



## THERMO-TAPE 840 T

### Product Information

Flexible PET-film with a high tack Silicon adhesive. The adhesive has an excellent resistance to chemicals, ageing, humidity and high temperature.

Suitable for positioning of Flock- and Flex-products before and during thermal transfer.

### Technical Data

Carrier:	PET-film, transparent	
Adhesive:	Silicon-PSA	
Adhesion [N/cm]:	5,20	+/- 10 %
Thickness [mm]:	0,09	+/- 5 %
Temperature-resistance [°C]:	max. 200	

### Standard Dimensions

9 mm x 66 m  
12 mm x 66 m  
19 mm x 66 m  
25 mm x 66 m

### Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

**POLI-TAPE Klebefolien GmbH**  
Zeppelinstraße 17  
53424 Remagen – GERMANY

Phone: +49 2642 – 98 36 0  
Fax: +49 2642 – 98 36 37

E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)  
Internet: [www.poli-tape.de](http://www.poli-tape.de)

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.