



UZLEX DS 3605

TECHNICAL DATA SHEET

UZLEX
WWW.UZLEX.EU

PRODUCT DESCRIPTION

Double-sided mounting tape based on a durable elastic, compressible foam carrier based on ethylvinylacetate. UZLEX DS 3605 offers a high initial tack even on rough and critical substrate surfaces such as polyethylene or polypropylene. Adhesive has a high resistance against ageing, UV and weathering.

APPLICATIONS

Especially to be emphasised are the following properties:

- Mounting of injection moulded and extruded plastic objects such as PVC cable trunkings, cover plates, hooks and holders.
- Mounting of displays, product samples, plates and screens.
- Self-adhesive mounting of unpolar plastics such as polyethylene, polypropylene and polystyrene.

TECHNICAL DATA

Adhesive type: Solvent acrylic

Adhesion [N/25mm]: 11,75 +/- 10 %

Carrier: EVA-foam, White

Liner: Silicone-paper, white

Thickness [mm]: 1,00 +/- 5%

Temperature resistance [°C]: +20 / +70

STANDART DIMENTIONS

6mm x 16,5m 19mm x 16,5m

9mm x 16,5m

12mm x 16,5m

SELF LIFE

When stored in the original packaging at 21°C and at 50% relative humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oil grease and dust.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of UZLEX, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. UZLEX makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.