



UZLEX DS 32112

TECHNICAL DATA SHEET

UZLEX
WWW.UZLEX.EU

PRODUCT DESCRIPTION

Double-sided clear acrylic thin tape with high tack has been developed for bonding glass, clear plastics and applications requiring an invisible bondline.

Beside an excellent adhesion, UZLEX DS 32112 offers good weather and UV-resistance.

It is soft, tacky and conformable. Acts as a very good seal and bonding tape.

APPLICATIONS

- solar energy industry,
- glass partitions,
- windows,
- doors and
- safety glass manufacture.

TECHNICAL DATA

Adhesive type:	Acrylic, Clear
Adhesion [N/25mm]:	25,00 +/- 10 %
Carrier:	Acrylic foam
Liner:	Red PE
Thickness [mm]:	0,5 +/- 0,1mm
Temperature resistance [°C]:	-40/+150(short) +90(long)

STANDART DIMENTIONS

9mm x 33m
12mm x 33m
19mm x 33m

SELF LIFE

When stored in the original packaging at 21°C and at 50% relative humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oil/grease and dust.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of UZLEX, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. UZLEX makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.