



UZLEX DS 32241

TECHNICAL DATA SHEET

UZLEX
WWW.UZLEX.EU

PRODUCT DESCRIPTION

Double-sided white acrylic 1,1mm thick tape with high tack and very high adhesion has been developed for heavy duty applications both in- and outdoor in any surface even for mounting parts on airplanes and boats, automotive etc.

Beside an excellent adhesion, UZLEX DS 32241 offers good weather and UV-resistance.

Other applications in the sign industry, construction industry and automotive aftercare market.

APPLICATIONS

- Mounting of automotive industry: plastics and painted steel
- Aircrafts and boats manufactory/ aftercare
- Sign industry long terms outdoor applications
- Construction industry etc.

TECHNICAL DATA

Adhesive type:	Acrylic, White
Adhesion [N/25mm]:	45,00 +/-10 %
Carrier:	Acrylic foam
Liner:	Red PE
Thickness [mm]:	1,1 +/- 0,1mm
Temperature resistance [°C]:	-40/+160(short) +100(long)

STANDART DIMENTIONS

9mm x 33m	25mm x 33m
12mm x 33m	
19mm x 33m	

SELF LIFE

When stored in the original packaging at 21°C and at 50% relative humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oilm grease and dust.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of UZLEX, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. UZLEX makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.